

### **JUMBO - Heber**

Der JUMBO- Heber ist ein äußerst robustes und kompaktes Werkzeug mit Ratschenantrieb.

Er hat sich besonders da bewährt, wo schwere Lasten in engen räumlichen Verhältnissen bewegt werden müssen.

Durch diese Vorteile und die verschiedenen Hubhöhen ist er eine echte Alternative zu Hydraulikzylindern, wobei er Umweltvorteile bietet und stromunabhängig arbeitet. Dabei hält er wie die DIN- Stahlwinde die Last in jeder Stellung fest.

Den „JUMBO“ gibt es auch mit Überlastsicherung!

### **Jumbo jack**

The JUMBO lifter is an extremely robust and compact tool with ratchet drive.

It has especially proven itself wherever loads need to be moved in tight spatial circumstances.

With this advantage and the various lifting heights, it is a genuine alternative to hydraulic cylinders while at the same time providing environmental benefits and power independence. And while doing so, it tightly holds the load in every position just like the DIN steel jacks.

„JUMBO“ is also available with overload protection!



# HEBEZEUGE

Tech. data and main dimensions		No. 11 JUMBO lifter		
Lifting force on head:		7,5 t		
Lifting force on claw:		4 t		
Installation height:	380 mm	480 mm	580 mm	
Lifting height:	200 mm	300 mm	400 mm	
Height of claw in lowest position		75 mm		
Weight:	20 kg	22 kg	24 kg	
No. 11 Without overload protection	1169020	1169030	1169040	
No. 11a With overload protection	1179020	1179030	1179040	