



Avanti – Daten & Fakten

Modell	AV-0.7	AV-1	AV-3	AV-5	AV-8	AV-10	AV-20	AV-35	AV-50
Drehmoment min. Nm	135	257	584	1.004	1.508	1.893	3.618	6.496	9.413
Drehmoment max. Nm	1.024	1.767	4.090	7.013	10.682	15.720	24.626	46.884	58.391
Vierkantantrieb Zoll	$\frac{3}{4}$	$\frac{3}{4}$	1	1 $\frac{1}{2}$	1 $\frac{1}{2}$	1 $\frac{1}{2}$	2 $\frac{1}{2}$	2 $\frac{1}{2}$	2 $\frac{1}{2}$
Drehmomentgenauigkeit %	± 2,5	± 2,5	± 2,5	± 2,5	± 2,5	± 2,5	± 2,5	± 2,5	± 2,5
Werkzeuggewicht kg mit 360°x 360° einstellbarem Reaktionsarm	2,74	3,00	6,70	10,70	13,20	19,40	31,00	56,40	64,00
Radius [R] mm	25,1	28,7	38,1	45,7	50,0	57,2	66,0	81,0	100,3
Länge [L] mm	82	99	127	156	171	191	223	272	315
Höhe [H] mm	83	97	122	145	158	177	203	241	272
Breite [B] mm	47	56	75	88	98	111	130	161	182

AVANTI - 1**Standard Druck Drehmomenttabelle**

Druck (bar)	Drehmoment (Nm)
100	257
120	308
140	359
160	411
180	466
200	518
220	570
240	620
260	671
280	723
300	774
320	824
340	876
360	927
380	975
400	1.023
420	1.074
440	1.125
460	1.172
480	1.223
500	1.274
520	1.321
540	1.368
560	1.419
580	1.470
600	1.517
620	1.567
640	1.618
660	1.666
680	1.717
700	1.767

R1-2012