

HYLOMAR[®]

THE original UNIVERSAL JOINTING COMPOUND

M

- Non-setting jointing compound.
- Temperature range -50°C to +250°C.
- Resistant to fuels, oils, coolants and gases.
- Specified worldwide by original equipment manufacturers for over 40 years.
- Hylomar Ltd - The ONLY manufacturer of Hylomar[®].










HYLOMAR®

THE original UNIVERSAL JOINTING COMPOUND

- Easy to use.
- Unlimited assembly time.
- Easy to disassemble components sealed with Hylomar.
- Use on metal to metal joint surfaces to replace conventional pre-formed gaskets.
- Use as a gasket dressing to improve the sealing performance of the gasket and to assist gasket alignment during assembly.
- Use as a non-curing thread sealant.
- Resists vibration.
- Approved for use in the following industries: automotive engines, transmissions, motor cycle engines, power generation, electric motors, pump manufacture, valve manufacturing, refineries, industrial radiators, tractors, chemical, mining, marine engines, railways, paper and packaging machinery and non-aerospace defence industries.
- The Hylomar products for aerospace applications are either Hylomar Aerograde or Aerograde Ultra.

Hylomar M is available in the following formats:

						
40ml TUBE on blister card 12 per case	80ml TUBE in carton 10 per display case	200ml AEROSOL 12 per case	200ml AUTOPRESS 12 per case	250ml BRUSH TOP TIN 12 per case	300ml CARTRIDGE 12 per case	1 litre TIN 10 per case

Hylomar Ltd

The only manufacturer of Hylomar®

Hylomar Ltd, Cale Lane, Wigan WN2 1JT, England
Tel: +44 (0)1942 617000 Fax: +44 (0)1942 617001
Web: www.hylomar.com Email: info@hylomar.com

